Product Data Sheet



Topolymer® RCC 8232-701N Styrenic Thermoplastic Elastomer

Product Description

Topolymer® RCC 8232-701N is a TPE compound based on Styrenic Block Copolymer (SBC). This material can be over-molded onto PP or used for single injection. This grade contains 25% PCR material, which is 100% recyclable.

General

Appearance √ Natural

Feature

√ Soft Touch

√ Silky Feel

√ Easy Coloring

√ Tear Resistance

Compliance √RoHS √REACH √FDA

Form √ Pellet
Packaging √ 25kg/bag

Technical Property

Typical Properties	Typical Value	Unit	Test Method
Hardness	70	Shore A	ASTM D2240
Density	0.89	g/cm³	ASTM D792
Tensile Strength at break	7	MPa	ASTM D412
Elongation at Break	700	%	ASTM D412
Tear Strength	30	KN/m	ASTM D624

The data are not to be defined as specifications.

Topolymer® RCC 8232-701N

Product Data Sheet

Processing Information

Injection	Typical Value	
Rear Temperature	170-180℃	
Middle Temperature	180-220℃	
Front Temperature	180-220℃	
Nozzle Temperature	190-230℃	
Mold Temperature	20-40℃	
Injection Rate	Fast/Medium	
Back Pressure	0.35-0.7MPa	
Screw Speed	30-80rpm	
Screw L/D Ratio	22:1	
Screw Compression Ratio	2:1-4:1	

Notes:

Contact Information

Top Polymer (China) tpe@topolymer.com www.topolymer.com

10 Xiyuan Rd, Tianmuhu Industrial Park Liyang, Jiangsu China

Tel: +86 (519) 8796 6118 Fax: +86 (519) 8796 6228 1017 Building 1, No. 1 Junma Street, Chigang Humen Town, Dongguan City, GuangDong

Tel: +86 (769) 8584 6000 Fax: +86 (769) 8584 6001

All information supplied by or on behalf of Top Polymer in relation to its products, whether in nature of data, recommendations or otherwise, is supported by research and believed reliable, but Top Polymer assumes no liability whatever in respect of application, processing or use made of the mentioned information or products, or any consequence. The buyer shall undertake all liability in respect of the application, processing or use of the mentioned information or products, or any consequence.

Rev. 2024-01-01

¹⁾ The product is incompatible with PVC. Purge thoroughly before and after use of this product with a low flow (0.5 - 2.5 MFR) Polyethylene (PE) or Polypropylene (PP).

²⁾ Color concentrate with PP, LDPE or EVA based carrier is recommended.

³⁾ Drying is not required. However, if moisture is a problem or to get better appearance, dry pellets for 3 hours at 60°C.